


Specifications:
 Current Rating:3.0A AC,DC
 Voltage Rating:250V AC,DC
 Contact Resistance:20mohm Max
 Insulation Resistance:1000Mohm Min.
 Withstanding Voltage:1000V AC/minute
 Operating Temperature Range:-40°C~+85°C
 Material And Finish:
 Insulator:Nylon 66 UL94V-0
 Insulator Color:White
 Contact:Brass
 Plated:Tin Plated
 How To Order:
 2317SJ-XX

No. Of Contacts
 SJ: Straight Type

Dimension:

POS.	Dim.A	Dim.B	POS.	Dim.A	Dim.B	POS.	Dim.A	Dim.B
2	2.50	7.50	9	20.00	25.00	16	37.50	42.50
3	5.00	10.00	10	22.50	27.50	17	40.00	45.00
4	7.50	12.50	11	25.00	30.00	18	42.50	47.50
5	10.00	15.00	12	27.50	32.50	19	45.00	50.00
6	12.50	17.50	13	30.00	35.00	20	47.50	52.50
7	15.00	20.00	14	32.50	37.50			
8	17.50	22.50	15	35.00	40.00			



PCB LAYOUT

RoHS Compliant

F				DRAWN: Zhou Lin	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	 中祥电子股份有限公司 Maltron Industrial Co., Ltd.	DESCRIPTION: 2.50mm Wire To Board Wafer Straight Type	SIZE A4
E			CHECKED: Jeremy Liu	UNIT: MM				
D				APPROVAL: Mike Wu	SCALE: 1:1	PART NO: 2317SJ-XX		
C					SHEET: 1 / 1			
B					PROJECTION:			
A	18-Jul-2008	(PC0001)	Zhou Lin					
REV	DATE	FILE	BY					